



OMNIAIRE 1300V

HEPA Air Filtration Machine

ORDERING INFO

OmniAire 1300V	OAI300V
Primary/Secondary Two-Stage Filters (box of 20)	OAP2614
HEPA FILTER 99.97%, 0.3µ (pb frame)	OAH2412
OdorGuard 600 Carbon Filter	OG2412D
ABS Plastic Intake Manifold, 10" Dia.	OAIM1300-10
Quick Clamp, 10" Dia.	QCW12
Flexible Duct, 10" Dia. x 25' L	OAD10
Flexible Duct, Wire & Fiber Reinforced	OADIOR

PART NUMBER



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

The OmniAire 1300V air scrubber with HEPA filter is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. This machine is only 15" wide and ideal for narrow hallways, hotel rooms and condos. Accessories include activated carbon filters for chemical fumes and biological contaminants, as well as intake manifold, flex ducting and quick clamps.

OmniAire 1300V

Airflow*	300/1250 CFM
Power Requirements	115 VAC/60 Hz/8.7 Amp
Motor	1 HP with thermal overload
Controls	HIGH/OFF/speed control switch; variable speed controller; hour meter; 0-5" W.C. pressure gauge
Filtration	HEPA 99.97%, 0.3 µ filter; MERV 9 primary/secondary filter Optional: OdorGuard 600 activated carbon filter
Housing	aircraft grade aluminum, silicone sealed before riveting; 10" outlet; (4) rubber grip handles; (4) 3" hospital grade locking casters
Size/Weight	15"W x 30"H x 34"L, 93 lbs.

*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.