



# OMNIAIRE 2000V

## HEPA Air Filtration Machine

### ORDERING INFO

OmniAire 2000V  
 Primary/Secondary Two-Stage Filters (box of 20)  
 HEPA Filter 99.99%, 0.3 $\mu$  (metal frame)  
 HEPA FILTER 99.97%, 0.3 $\mu$  (pb frame)  
 Bag Filter Housing (includes 1 Bag Filter)  
 Bag Filter MERV 15  
 Vapor Trap V-bank Filter  
 OdorGuard 600 Carbon Filter  
 Intake Manifold Kit (Manifold, Clamp & 3' Duct)  
 ABS Plastic Intake Manifold, 12" Dia.  
 Quick Clamp, 12"-16" Dia.  
 Flexible Duct, 12" Dia. x 25' L  
 Flexible Duct, Wire & Fiber Reinforced

### PART NUMBER

OA2000V  
 OFP2518  
 OAH2418G  
 OAH2418  
 HBF2000  
 OBF9  
 OCVT18  
 OG2418D  
 OAIM2000-12KIT  
 OAIM2000-12  
 QCW14  
 OAD12  
 OAD12R



CONFORMS TO UL STD 507  
 CERTIFIED TO CAN/CSA STD  
 C22.2 NO. 113-M1984

The OmniAire 2000V is a compact and versatile, variable speed HEPA air filtration machine/air scrubber that delivers the performance of full size negative air machines. It is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects, and for purifying air in commercial, factory sites and medical facilities. Designed and built with multiple filter options including HEPA, 8-Pocket Bag filter for construction dust, and activated carbon filters to meet your job requirements. Additional accessories include intake manifold, flex ducting and quick clamps.

### OmniAire 2000V

<b>Airflow*</b>	400-1600 CFM
<b>Power Requirements</b>	115VAC/60 Hz/10.6 Amp
<b>Motor</b>	1.25 HP with thermal overload
<b>Controls</b>	speed switch - HIGH/OFF/Speed Control; variable speed controller; 0-5" W.C. pressure gauge; red power indicator light
<b>Filtration</b>	HEPA filter 99.97% @ 0.3 $\mu$ ; MERV 9 primary/secondary filter Optional: MERV 15 bag filter; OdorGuard 600 activated carbon web filter; VaporTrap V-bank filter (27 lbs of active carbon); HEPA filter 99.99% @ 0.3 $\mu$
<b>Housing</b>	aircraft grade aluminum; silicone sealed before riveting; 12" outlet; (4) rubber grip handles; (2) 5" hospital grade locking casters; (2) 5" rigid casters
<b>Size/Weight</b>	22"W x 32"H x 34"L; 117 lbs.

\*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.