



## OMNIAIRE 600V HEPA Air Filtration Machine

### ORDERING INFO

OmniAire 600V  
Primary/Secondary Two-Stage Filters (box of 20)  
HEPA Filter 99.99%, 0.3 $\mu$  (metal frame)  
HEPA FILTER 99.97%, 0.3 $\mu$  (pb frame)  
OdorGuard 600 Carbon Filter  
Intake Manifold Kit (Manifold, Clamp & 3' Duct)  
ABS Plastic Intake Manifold, 8" Dia.  
Quick Clamp, 8"-10" Dia.  
Flexible Duct, 8" Dia. x 25' L

### PART NUMBER

OA600V  
MFPI313  
MFH12G  
MFH12  
OG1212  
MFIM8KIT  
MFIM8  
QCW12  
MD8



CONFORMS TO UL STD 507  
CERTIFIED TO CAN/CSA STD  
C22.2 NO. 113-M1984

The OmniAire 600V is a compact, versatile air scrubber with high airflow and variable speeds. It is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects, and for purifying air in commercial or factory sites and medical facilities. This popular, light-weight machine is made of strong aircraft grade aluminum housing with smooth surfaces for easy sanitation. It can be used with multiple filter options such as HEPA, activated carbon plus MERV 9 primary/secondary filter. Additional accessories include intake manifold, flex ducting and quick clamps.

### OmniAire 600V

<b>Airflow*</b>	150-550 CFM
<b>Power Requirements</b>	115VAC/60 Hz/2.3 Amp
<b>Motor</b>	0.25 HP with thermal overload
<b>Controls</b>	variable speed controller; 0-3" W.C. pressure gauge
<b>Filtration</b>	HEPA filter 99.97% @ 0.3 $\mu$ ; MERV 9 primary/secondary filter Optional: OdorGuard 600 activated carbon web filter; HEPA filter 99.99% @ 0.3 $\mu$
<b>Housing</b>	aircraft grade aluminum; silicone sealed before riveting; 8" outlet; (2) rubber grip handles; (4) 3" hospital grade locking casters
<b>Size/Weight</b>	14"W x 19"H x 31"L; 58 lbs.

*\*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.*